

PFT MULTIMIX 140 plus


The multi-component mixer for the professional

The powerful batch mixer, which is particularly suitable for special mixtures of different components. Strong mixing arms save time for a homogeneous mortar mixture. Clever in the system – the mixed material is delivered to a PFT conveying pump, which transports the pumpable material directly to the processing place.



TECHNICAL DATA

Part no.	00251636
Mixing capacity	80 l/batch
Grain size	max. 8 mm
Motor	400 V, 3 Ph, 50 Hz, 2.2 kW, 56 rpm
Mixing hopper	Steel
Water connection	Geka DN19 – 2.5 bar operating pressure
Operation and control	Start/Stop
Filling height	1,120 – 1,380 mm
Outlet height	400 – 720 mm, adjustable
Hopper content	140 l
Dimensions: L/W/H	980 / 1,060 / 1,380 mm
Weight	~148 kg



ADVANTAGES AT A GLANCE



- Easy handling
- Minimal maintenance and cleaning effort
- Self-cleaning mortar outlet
- Phase converter in main switch
- Opposite agitators
- Turbo mixing system
- Robust design for construction site
- Height adjustable
- Fits easily over a conveying pump such as the ZP 3 or SWING

FIELDS OF APPLICATION

- Concrete restoration
- Powder adhesive
- PCC- and SPCC-mortar
- Mineral plaster
- Fine-grained concrete
- Acoustic plaster
- Screed
- Artificial resin plaster
- Masonry
- Granulates
- Loam plaster
- Furnace construction

ACCESSORIES

- Extension cable 5 x 2.5 mm², RED 5-16 A – 25 m
- Water pump AV 1000 standalone 230 V, 1 Ph, 50 Hz, 0.6 kW
- Suction strainer with filter screen
- Water hose/air hose DN12 Geka | Geka – 5 m
- Spray nozzle DN19 Geka

PART NO.

- 20423360
- 00493686
- 00136619
- 20211100
- 20215700

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT MULTIMIX 140 plus – EN/10.22/PFT