

PFT ZP 3 L MULTIMIX


Powerful pump with an integrated batch mixer

The conveying pump for individual job-site mixtures on-site. The pre-mixed plaster and masonry mortar are pumped directly to the point of application. The conveying capacity can be infinitely adjusted to the material requirements.



TECHNICAL DATA

Part no.	00280802
Conveying output	10 – 40 l/min, continuously adjustable
Conveying distance	up to 60 m
Working pressure	max. 20 bar
Rotor/ Stator	RENDER STAR
Motor	400 V, 3 Ph, 50 Hz, 5.5 kW, 70 – 260 rpm
Material outflow	DN50 female part
Material hose	RONDO DN35 – 10 m
Adapter coupling	35 female 50 male part
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW, 250 l/min
Spraying gun	DN35 M20 Geka
Water/air hose	DN12 Ewo Geka – 11 m DN12 Geka Geka – 11 m
Filling height	630 mm
Hopper content	140 l
Dimensions: L/W/H	2,200 / 860 / 1,100 mm
Weight	~370 kg



ADVANTAGES AT A GLANCE



- Integrated pressure remote control – allows on/off machine control via the air supply at the spraying device
- Pump performance continuously adjustable via vario gearbox
- Variable delivery performance through pump change (L or R pump)
- Cleaning port in material hopper
- Solid rubber wheels with steel rims
- Double gearbox seal with inspection opening
- Optional: agitator screen
- Pump shaft mixes material again – no separation in the pump
- Robust metal sheet protects motor and gearbox
- Hopper with optimised emptying – no residual quantities
- Batch mixer integrated
Motor: 2.2 kW, 56 rpm
- Crane eyes

FILEDS OF APPLICATION

- Job-site mixtures
- Lime-cement render
- Loam plaster
- Concrete refurbishment
- Masonry mortar
- Fire protection mortar
- Adhesive mortar
- Grouting mortar
- Levelling compound
- Floor screed
- Thin screed

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A – 50 m
- Remote control cable – 25 m
- Vibrating screen for retrofitting
- Nozzle DN19 Geka
- Purge hose DN10 Geka – 11 m
For cleaning of material hoses

PART NO.

- 20423900
- 20456929
- 00255376
- 20215700
- 00113856

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 L MULTIMIX – EN/10.22/PFT