

# PFT ZP 3 XL FC-400V

## The universal suitable conveying pump


The conveying pump conveys mixed plaster, masonry mortar or screed, through a continuous mixer or a batch mixer, directly to the construction site. Depending on the material requirements, the pump capacity can be adjusted without any restrictions.



### TECHNICAL DATA

Part no.	00 10 29 57
Working pressure	max. 30 bar
Conveying capacity	12 - 42 litres/min
Conveying distance	up to 100 m
Motor	400 V, 3 Ph, 50 Hz, 7.5 kW, 84 - 280 rpm
Hopper content	130 litres
Rotor / Stator	R 7-3 S
Grain size	max. 7 mm
Material outflow	DN50 female part
Filling height	620 mm
Dimensions: L/W/H	2,255/725/745 mm
Weight	~240 kg

**Kindly note:**  
All details depends on the used materials.



## ADVANTAGES AT A GLANCE



- Variable conveying capacity through pump change (L or R pump)
- Solid rubber wheels with steel rims
- Double gearbox seal with inspection opening
- Cleaning port in material hopper
- Pump performance continuously adjustable via frequency converter
- Optional: Vibrating screen
- Crane lifting eyes

### FIELDS OF APPLICATION

- Masonry mortar
- Light masonry mortar
- Reinforcing mortar
- Screed mortar
- Glueing mortar
- Tiling and filling mortar
- Cement plaster
- Insulation plaster
- Loam plaster
- Floating plaster
- Restoration plaster
- Scratch coat

### ACCESSORIES

- Extension cable 5 x 4 mm<sup>2</sup>, RED 5-32 A – 25 m
- Remote control cable with switch – 25 m
- Vibrating screen for retrofitting
- Retrofit kit for air compressor
- Water hose Geka | Geka DN12 – 5 m
- Extension hopper 300 mm

### PART NO.

- 20 42 39 20
- 20 45 69 29
- 00 14 81 46
- 00 15 11 79
- 20 21 11 00
- 00 09 80 04

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpft](http://www.youtube.com/knaufpft)

Download now! APP: PFT – Plastering Technology

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 XL FC-400V – EN/04.19/PFT