

PFT ZP 3 XXL FC-400V


The robust with unbeatable conveying capacity

With a conveying capacity of 180 l/min the conveying pump can handle many applications. Whether high or far the ZP 3 XXL pumps the plaster, masonry mortar or screed directly to the construction site.



TECHNICAL DATA

Part no.	00151174
Conveying capacity	15 - 180 l/min
Conveying distance	up to 150 m
Working pressure	max. 20 bar
Rotor / Stator	SOLVER 2 L 8
Grain size	max. 14 mm
Motor	400 V, 3 Ph, 50 Hz, 13 kW, 14 - 162 rpm
Material outflow	DN65 male part
Filling height	620 mm
Hopper content	130 l
Dimensions: L/W/H	3,075/725/745 mm
Weight	~390 kg



ADVANTAGES AT A GLANCE



- Pump performance continuously adjustable via frequency converter
- Long pressure flange for grain size up to 16 mm
- High conveying capacity and distance
- Robust and compact
- Solid rubber wheels with steel rims
- Double gearbox seal with inspection opening
- Cleaning port in material hopper
- Control unit with vibrator control integrated

FIELDS OF APPLICATION

- Masonry mortar
- Light masonry mortar
- Floor screed (from truck mixer)
- Levelling compound
- Spraying concrete

ACCESSORIES

- | | |
|---|----------|
| ■ Extension cable 5 x 6 mm ² , RED 5-32 A – 25 m | 00105633 |
| ■ Remote control cable with switch – 25 m | 20456929 |
| ■ Extension hopper 300 mm | 00098004 |
| ■ Water hose/air hose DN12 Geka Geka – 5 m | 20211100 |
| ■ Spray nozzle DN19 (3/4") Geka | 20215700 |
| ■ Purging hose DN10 Geka – 11 m | 00113856 |

PART NO.

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 XXL FC-400V – EN/10.22/PFT