

PFT HM 106

The compact continuous mixer with small dimensions


The continuous mixer has been especially designed for use with small container. Thanks to its compact dimensions the mixer can be flanged on the silo/container during transport.






TECHNICAL DATA

Part no.	00 05 75 09
Conveying output	max. 20 - 50 litres / min
Water flow meter	with gauge
Motor	230 V, 1 Ph, 50 Hz, 3 kW, 280 rpm
Mixing tube	rubber mixing tube
Water connection	Geka DN12 - 2.5 bar operating pressure
Operation and control	start / stop
Grain size	max. 6 mm
Dimensions: L/W/H	1,300/210/500 mm
Connection flange	Ø 250 mm
Weight	~ 82 kg without control unit

Kindly note:
 Conveying distance depends on the used materials.



ADVANTAGES AT A GLANCE

		<ul style="list-style-type: none"> 1 Removeable mortar outlet 2 Perfect teamwork between screw mixer and conveying pump 3 Removeable control unit 4 Removeable rubber mixing tube 5 Comfortable transport flanged to silo/container 6 Easy mounting to silo/container thanks to Ø 250 mm connection flange <ul style="list-style-type: none"> ■ Minimum effort for maintenance and cleaning ■ Constant mixing quality ■ Silo mixer ■ Easy handling ■ Also available as 400 V version
		
		
		
		
		

FIELDS OF APPLICATION

- Bonding and reinforcing mortar
- Masonry mortar
- Grouting mortar
- Plastering mortar
- Screed mortar
- Levelling compound
- Finishing coat



ACCESSORIES

PART NO.

- | | |
|--|-------------|
| ■ Extension cable 3 x 2,5 mm ² ,
BLU 2-16 A - 25 m | 20 42 34 00 |
| ■ Water hose DN12
Geka / Geka- 20 m | 20 21 20 10 |
| ■ Spray nozzle DN19 Geka | 20 21 57 00 |

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.eu
www.youtube.com/knaufpften

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft-iphofen.de www.pft.eu

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT HM 106 - GB/12.16/PFT