

# PFT HM 24


## The clever bagged material and silo mixer

The allrounder among the continuous mixers. It is especially suitable for the application of adhesive mortars. The PFT HM 24 is characterized by its easy handling.



### TECHNICAL DATA

Part no.	00020357
Mixing capacity	max. 20 - 50 l/min
Grain size	max. 6 mm
Motor	400 V, 3 Ph, 50 Hz, 3.3 kW, 280 rpm
Mixing tube	Rubber mixing tube
Pedestal	fix
Wheels	2 wheels
Water connection	DN12 Geka - 2.5 bar at running machine
Operation and control	Start/Stop
Filling height	970 mm
Output height	650 mm
Hopper content	110 l
Dimensions: L/W/H	1,870/670/970 mm
Weight	~ 135 kg



**PFT – ALWAYS AT YOUR SITE**

## ADVANTAGES AT A GLANCE



- 1** Removeable mortar outlet
- 2** Water manifold with pressure reducer
- 3** Perfect interaction between screw mixer and conveying pump
- 4** Silo and container transfer is possible by an delivery hood (Part no. 20600500)
- Minimal maintenance and cleaning overhead
- Easy to transport
- Phase inverter in connection plug
- Rubber mixing tube: no caking of the materials
- Easy operation
- Constant mixing quality

### FIELDS OF APPLICATION

- Masonry mortar
- Light masonry mortar
- Reinforcing mortar
- Scratch coat
- Cement plaster
- Insulation plaster
- Screed mortar
- Levelling compound
- Adhesive mortar
- Grater mortar
- Restoration plaster
- Tiling and jointing mortar
- High-grade plaster

### ACCESSORIES

- |   | PART NO. |
|---|----------|
| ■ Extension cable 5 x 2.5 mm <sup>2</sup> , RED 5-16 A – 50 m | 20423350 |
| ■ Water hose/air hose DN19 Geka   Geka – 40 m                 | 20212100 |
| ■ Spraying cap DN19 Geka                                      | 20215700 |
| ■ Extension hopper – 142 litres                               | 00453469 |
| ■ Cover for material hopper                                   | 00201267 |
| ■ Mixing shaft HM 24, earth-moist materials                   | 00513092 |

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpft](http://www.youtube.com/knaufpft)

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

[info@pft.net](mailto:info@pft.net) [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT HM 24 – EN/10.22/PFT