

PFT LOTUS XS

The small, handy and economic continuous mixer


The PFT LOTUS XS is suitable for all dry mortars up to a grain size of 4 mm. For everybody, who likes to mix efficient and with a high standard – in PFT quality for a special price! In addition to the versions with steel mixing tube, machines with easy-to-clean rubber mixing tube are also available.



TECHNICAL DATA

Part no.	Machine type
00246057	LOTUS XS mortar (Steel mixing tube)
00754072	LOTUS XS r mortar (Rubber mixing tube)
00754070	LOTUS XS filler (Steel mixing tube)
00754071	LOTUS XS r filler (Rubber mixing tube)

Conveying capacity	max. 20 l/ min
Motor	230 V, 1 Ph, 50 Hz, 1.3 kW, 280 rpm
Mixing tube	Steel / Rubber mixing tube
Wheels	2 wheels
Water connection	Geka DN12 – 2.5 bar operating pressure
Operation and control	Start / stop
Filling height	1,010 – 1,150 mm, height-adjustable
Outlet height	570 – 710 mm, adjustable
Hopper content	50 liters
Dimensions: L / W / H	1,240 / 635 / 1,010 – 1,150 mm
Total weight	~ 74 kg



ADVANTAGES AT A GLANCE



- 1 Uncomplicated conversion of the LOTUS XS from steel to rubber mixing tube and vice versa
- 1 Convenience transport – handle on mixing tube
- 2 Simple and fast changeover from mortar to filler finish and vice versa
- 3 Optional water flow meter retrofittable*
- 4 Removable pedestal
- 5 Water manifold with pressure reducer
- Easy and thorough cleaning and also prevention of deposited material due to rubber mixing zone**
- Transport is possible in any estate car
- Minimal maintenance and cleaning effort
- Reach-in protected mortar outlet
- Constant mixing quality
- Easy filling of a conveying pump, mortar bucket or wheelbarrow with the LOTUS XS

* already included in the scope of delivery of LOTUS XS for filler applications
 ** concerns the versions LOTUS XS r (Part no. 00754071 filler and 00754072 mortar)



FIELDS OF APPLICATION

- Tilling and jointing mortar
- Light masonry and masonry mortar
- Adhesive and reinforcement mortar
- Screed mortar
- Levelling compound
- Scratch render
- Cement and insulation plaster
- Restoration and fine render

ACCESSORIES

- Extension cable 3 x 2.5 mm², BLA 2-16 A – 25 m
- Water hose DN19 Geka | Geka – 40 m
- Retrofit kit for water flow meter 100 - 1,000 l/h
- PFT TROLLEY – tipping trolley
- Conversion kit from steel mixing tube to rubber mixing tube
- Conversion kit for filler application
- Conversion kit for mortar application

PART NO.

- 20423400
- 20212100
- 00514763
- 00535699
- 00767145
- 00767144
- 00767143



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT LOTUS XS – EN/04.23/PFT