

PFT RITMO XL FC-230/400V


Powerful mixing pump

The PFT RITMO XL stands for more power, stronger pump unit, more processing possibilities. With the flexible choice between 230 V and 400 V combines the benefits of the bestseller PFT G 4 and the spraying technology of RITMO family.

TECHNICAL DATA

Part no.	00 19 78 21
Max. working pressure	25 bar
Max. conveying capacity	continuously adjustable from 20 l/min
Max. conveying distance	up to 30 m
Motor	230/400 V, 1/3 Ph, 50 Hz, 5.5 kW - 120 - 400 rpm
Hopper content	70 l
Connection cable	Adapter plug RED 5-32 A BLU 2-16 A
Rotor/Stator	SD 6-3 slimline
Spraying gun	DN25-360° S14 200 Geka
Air compressor	COMP P-200, 230 V, 1 Ph, 50 Hz, 0.5 kW, 200 l/min
Material outflow	DN25 male part
Material hose	RONDO DN25 - 10 m
Dimensions: L/W/H	1,300/700/1,400 mm
Filling height	850 - 1,010 mm
Weight	~232 kg

Kindly note:
Conveying distance depends on the used materials.



ADVANTAGES AT A GLANCE



- 1 Suitable for buckets and bags
- 2 Rubber mixing zone for easy cleaning with adapter flange for D- and R-pump
- 3 Flexible mixing intensity thanks to two water inlets
- Switchable 230 V and 400 V
- Conical mixing tube for optimum material flow
- Ready for remote control
- Powerful and reliable operation via standard power socket
- Easy dismantlable into three modules
- Tool box including basic accessories
- Variable filling height
- Frequency converter (FC) for infinitely variable speed control

FIELDS OF APPLICATION

- Lime-gypsum plaster
- Cement plaster
- Masonry mortar
- Insulation plaster
- Adhesive mortar
- Floor screed
- Levelling compound

ACCESSORIES

- Extension cable 3 x 2.5 mm², BLU 3-16 | BLA 2-16 A - 25 m
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo
- Spraying set finishing coats
- Hopper extension - up to 140 litre
- Cover for RITMO XL

PART NO.

- 20 42 34 20
- 00 42 00 58
- 00 41 89 75
- 00 23 21 06
- 00 20 18 70
- 00 20 79 57



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpften

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 DE-Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT RITMO XL FC-230/400V-EN/03.21/PFT