

PFT DUSTCATCHER G 4

Dust free - work clean and health-friendly

The dust formation during the loading of bagged goods cannot be completely prevented, but we can significantly reduce it. This is because the health of the processor is our priority.



TECHNICAL INFORMATION / DATA

Part no.	00539716
Dimensions: W / L	725 mm / 665 mm
Opening dimension: W / L	330 mm / 400 mm
Weight of hood	16.1 kg
Weight of deflector plate	2.3 kg
Connection vacuum cleaner	Internal diameter 37 mm
Power input	maximum 1,400 Watt
Hopper content for dust	25 litres

Dust remover: Category M - iPulse

Reduction efficiencies of filter system > 99.9%

Suitability for hazardous dust with
limit values² > 0.1 mg / m³

Scope of supply

- Dust remover, category M- iPulse¹
- Supplementary set of dust remover
comprises: 1x handhold, 2x suction tube,
1x joint nozzle, 1x dust nozzle
- Hopper extension DUSTCATCHER
- Deflector plate G 4 with outlet connections

¹ Source: EN 60335-2-69 and IEC 60335-2-69 Annex AA

² The corresponding national specifications must be taken into
consideration for the limiting values e.g. the TRGS 900 in Germany.

* up to 80% less dust



PFT – ALWAYS AT YOUR SITE

ADVANTAGES AT A GLANCE



- 1** Low overall height -
Filling height increases by approx. 2 cm
- 2** Floating dust is caught again through another
adjustable suction nozzle
- 3** Deflector plate G 4 with outlet connection
- 4** Including adjusting screw for mixing tube
- 5** Simple assembly using clever
hook screw
- 6** Robust integrated bag opener
- 7** Suitable for all G 4 types

SCOPE OF SUPPLY | ACCESSORIES

PART NO.

■ Dust remover, category M - iPulse ¹	00623276
■ Supplementary set of dust remover M - iPulse comprises: 1x handhold, 2x suction tube, 1x joint nozzle, 1x dust nozzle	00426894
■ Deflector plate for G 4 with outlet connection	00538445
■ Deflector plate for G 4 (with frame 3/4") with outlet connection	00659138
■ Extension hopper DUSTCATCHER	00538416
■ DUSTCATCHER for G 4 XL	00617274
■ DUSTCATCHER for G 4 (with frame 3/4")	00659260

¹ Source: EN 60335-2-69 and IEC 60335-2-69 Annex AA



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/dustcatcher
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT DUSTCATCHER G 4 - EN/04.23/PFT