


# PFT SILOMAT trans plus bag

Perfect for job sites without space for silos

No place on the job site? With the SILOMAT trans plus bag large amounts of material can be transported without an silo. All with one – the compact conveying unit for material in bags and also in silos.



TECHNICAL DATA	
Part no.	00689527
Conveying distance	140 m
Conveying output	20 kg/min
Motor	400 V, 3 Ph, 50 Hz
Compressor	Capacity: 7.5 kW Max. Pressure: 2.5 bar Air flow: 145 Nm <sup>3</sup> /h
Conveying pot content	60 l
Filling height	950 mm
Dimensions: L/W/H	1,150/660/745 mm
Weight	~ 305 kg



## ADVANTAGES AT A GLANCE

- 1** Fluidiser: Boosts and ensures the material flow; the vessel is nearly completely emptied
  - Maintenance-free
  - Resistant to humidity
  - Can be retrofitted
  - Performance increase by up to 30 %
- 2** Compressor is a dry running; no oil change needed
- 3** Crane transport eyes and fold-out carrying handles
- 4** Suitable for container/silo discharge flange Ø 250 mm
- 5** Easily replaceable seals
- 6** Socket for lift truck
- 7** Socket for fork lift

- Bypass: manually controllable for stiff materials and longer delivery reaches
- Long machine running times with a high level of operational reliability
- Easy replacement of wear parts – also on site
- Shut-off valve with actuator and handwheel
- Rotary compressor: as rollable and portable execution available
- Lateral de-aeration in the pot – speeds up and secures the filling procedure, no air cushion formation in the pot

### FIELDS OF APPLICATION

- Gypsum-lime plaster
- Cement render
- Lime plaster
- Masonry mortar
- Machine-applied gypsum plaster
- Bulk material
- Ingredients
- Powder material
- Lime cement plaster
- ... and many more

### ACCESSORIES

### PART NO.

- |  |          |
|--|----------|
| ■ Conveying hose - initial equipment – 73.3 m, consisting of | 00473424 |
| • 1 x Rubber conveying hose RONDO air 3-layer DN45 – 13,3 m  |          |
| • 3 x Rubber conveying hose RONDO air 3-layer DN45 – 20 m    |          |
| • Hose holder with hook                                      |          |
| ■ Extension cable 5 x 4 mm <sup>2</sup> , RED 5-32 A – 25 m  | 20423920 |
| ■ Cover for conveying pot                                    | 00201267 |
| ■ DUSTCATCHER G 4 complete                                   | 00539716 |
| ■ Adapter for silo connection                                | 00195080 |
| ■ Conversion kit – portable to rollable                      | 00129592 |

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpft](http://www.youtube.com/knaufpft)

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SILOMAT trans plus bag – EN/10.22/PFT