

PFT SILOMAT trans plus 145

The compact and transport-friendly conveying unit



The SILOMAT trans plus conveys dry mortar in a fully automatic and dust-free procedure. With very little effort the machine can be established and transported.

TECHNICAL DATA


Part no.	00689524
Conveying distance	140 m
Conveying output	20 kg/min
Motor	400 V, 3 Ph, 50 Hz
Compressor	Power: 7.5 kW Max. pressure: 2.5 bar Air volume: 145 Nm ³ /h
Capacity of conveying pot	55 l
Dimensions: L/W/H	1,100/635/720 mm
Weight	~ 275 kg

Kindly note:

Conveying distance depends on the used materials.



ADVANTAGES AT A GLANCE







- 1** Fluidiser: Boosts and ensures the material flow; the vessel is nearly completely emptied
 - Maintenance-free
 - Resistant to humidity
 - Can be retrofitted
 - Performance increase by up to 30 %
- 2** Compressor is a dry running; no oil change needed
- 3** Rotary compressor: as rollable and portable execution available
- 4** Crane transport eyes and fold-out carrying handles
 - Suitable for container/silo discharge flange Ø 250 mm
 - Shut-off valve with actuator and handwheel
 - Easily replaceable seals
 - Bypass: manually controllable for stiff materials and longer delivery reaches
 - Long machine running times with a high level of operational reliability
 - Easy replacement of wear parts – also on site

FIELDS OF APPLICATION	
■ Gypsum-lime plaster	■ Bulk material
■ Cement render	■ Aggregate
■ Lime plaster	■ Ingredients
■ Masonry mortar	
■ Machine-applied gypsum plaster	

ACCESSORIES / VERSIONS	PART NO.
■ Conveying hose - initial equipment - 73,3 m	00473424
1x Rubber conveying hose RONDO air 3-layer DN45 - 13,3 m	
3x Rubber conveying hose RONDO air 3-layer DN45 - 20 m	
1x Hose holder with hook	
■ Injection hood, foldable for G 4	00420664
■ Filling hopper for bagged material	20716000
■ Extension cable 5 x 4 mm ² , RED 5-32 A - 25 m	20423920
■ SILOMAT trans plus 145, rollable	00124358

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SILOMAT trans plus 145 - EN/06.21/PFT