

PFT ZP 3 M FC-230V

The small solution for big challenges

The smallest member of the ZP 3 conveying pump family is characterized by a compact design, a low weight and an optimum production of almost all construction mixtures.



TECHNICAL DATA

Part no.	00542526
Conveying capacity	8 - 33 l/min, continuously adjustable
Conveying distance	up to 60 m
Working pressure	max. 20 bar
Rotor/Stator	SOLVER 2 L 6
Motor	230 V, 1 Ph, 50 Hz, 4 kW, 40 - 190 rpm
Material outflow	DN35 female part
Material hose	RONDO DN35 - 10 m
Air compressor	COMP P-200, 230 V, 1 Ph, 50 Hz, 0.5 kW, 200 l/min
Spraying gun	DN35 S16 male part Geka
Water/air hose	DN12 Ewo male part Geka - 11 m
Filling height	635 mm
Hopper content	85 l
Dimensions: L/W/H	1,770/625/660 mm
Weight	~197 kg

*Image similar





230 V



4.0 kW



1 Ph



8-33 l/min

ADVANTAGES AT A GLANCE



- 1** Wide base tyres - good mobility
 - 2** Integrated pressure control for compressor
 - 3** Folded protection grille with switch-off function
 - 4** Two handles on the material hopper
 - 5** Handle at the pressure flange
 - 6** Integrated compressor console and hook
 - 7** Optionally: Vibrator screen
 - 8** Better cleaning of the machine and the cleaning opening by C-coupling - material hopper runs empty
- Machine shutdown via remote switch
 - Flow-optimized material hopper

Images similar

FIELDS OF APPLICATION

- Jobsite mixture
- Screed mortar
- Cement plaster

ACCESSORIES / VERSIONS

- Extension cable 3 x 2.5 mm², BLU 3-16 A | BLA 2-16 A - 25 m
- Remote control cable with switch - 25 m
- Water hose DN12 (1/2") Geka | Geka - 5 m
- Spray nozzle DN19 (3/4") Geka
- Vibrating screen for retrofitting 230 V
- ZP 3 M pole-changing
- ZP 3 M FC-400V

PART NO.

- 20423420
- 20456929
- 20211100
- 20215700
- 00541174
- 00542528
- 00542527



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 M FC-230 V - EN/10.22/PFT