

PFT RITMO L FC-230V plus – B 4 – 2


The all-rounder for every challenge

No matter how compact the construction site, how demanding the renovation, how daring the schedule – with the PFT mixing pump you will easily understand. You are also very flexible on your own, completely mobile – and in no time you will be the hero for your client.



TECHNICAL DATA

Part no.	00659504
Conveying capacity	up to 14 litres/min, continuously adjustable
Conveying distance	up to 20 m
Working pressure	max. 20 bar
Rotor/Stator	B 4 – 2
Motor	230 V, 1 Ph, 50 Hz, 2.4 kW, 55 – 492 rpm
Mixing tube	Rubber
Material outflow	DN25 male part
Operation	Compressor: pressure control
Material hose	RONDO DN25 – 15 + 5 m
Air compressor	COMP R-80, 230 V, 1 Ph, 50 Hz, 0.35 kW, 80 l/min
Spraying gun	DN25-360° S10 200 Ewo
Connection cable	BLU 3-16 A BLA 2-16 A – 25 m
Water/air hose	DN12 Geka Geka – 11 m
Air hose	DN9 Ewo Ewo – 16 + 5 m
Filling height	930 mm
Hopper content	45 l
Dimensions: L/W/H	915 / 600 / 1,450 mm
Weight	~ 135 kg



ADVANTAGES AT A GLANCE

		<p>1 Suitable for bucket and bag material</p> <p>2 Flow-optimized output</p> <p>2 Mortar pressure gauge integrated</p> <p>3 Rubber mixing zone for easy cleaning with adapter flange for A-, B- and D-pump</p> <p>4 Easy dismantlable into single modules</p> <ul style="list-style-type: none"> - Motor with tilt flange (a): 30 kg - Material hopper with pump unit (b): 28 kg - Chassis (c): 64 kg - Mixing shaft (d): 3 kg
		<p>4 In series equipped with external vibrator</p> <p>5 Flexible mixing intensity thanks to two water inlets</p> <p>6 Easy handling on start-up, retrofitting, maintenance and cleaning</p> <p>6 Foldable motor</p> <p>6 Circumferential sealing edge on the material container for accessories</p>
		<p>7 Transport is possible in any estate car</p> <ul style="list-style-type: none"> ■ Mounting position for Rotor/Stator mounting ■ Conical mixing tube for optimum material flow ■ Large insertion area ■ Runs powerfully and reliably with luminous flux ■ Extension hopper – for double volume

FIELDS OF APPLICATION

- Interior plaster
- Finishing coat
- Floor levelling compound
- Fine filler
- Adhesive / reinforcement mortar
- Fire protection mortar
- Grouting mortar

ACCESSORIES | SPARE PARTS

	PART NO.
■ Extension cable 3 x 2.5 mm ² , BLU 3-16 A BLA 2-16 A - 25 m	20423420
■ Extension hopper for RITMO L plus	00612729
■ DUSTCATCHER for material hopper RITMO L plus	00611177
■ DUSTCATCHER for extension hopper RITMO L plus	00619834
■ Mixing shaft BIONIK RITMO L plus , D=76 mm	00705754
■ Stator B 4-2 mf	00008462
■ Rotor B 4-2	00245810

Further accessories and spare parts could be found at www.pft.net/plus



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand-with its sales and service centers worldwide-stands for also in the coming decades.



Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

RITMO L plus - B 4-2 - EN/10.22/PFT