

PFT SILOMAT XXL-D


The problem solver for hard-moving material

Designed for coarse, hard-moving material. The premixed dry mortar is uniformly introduced into the conveying hose and blown continuously to the processing site. The integrated anti-tamper control allows time and cost-saving work.




TECHNICAL DATA

Part no.	00606758	50 Hz
	00603707	60 Hz
Conveying distance / conveying output	25 m	28 kg/min
	50 m	24 kg/min
	100 m	15 kg/min
Dosing shaft	30 l/min	
Power connection	400 V, 3 Ph, 50/60 Hz	
Compressor		
Capacity	7.5 kW	50 Hz
	9.0 kW	60 Hz
Pressure max.	2.5 bar	
Air flow	122 Nm ³ /h	50/60 Hz
Silo connection	Ø 250 mm	
Dimensions: L/W/H	1,150/660/745 mm	
Conveying pot height	1,010 mm	
Conveying pot content	50 l	
Weights	~ 230 kg	compressor
	~ 135 kg	conveying pot
	~ 365 kg	total weight



ADVANTAGES AT A GLANCE

 <p>1 Large wheels for easy jobsite handling and silo assembly</p>	 <p>1 Dosing shaft for constant dosing of the premixed dry mortar into the air stream</p>	<ul style="list-style-type: none"> 1 Suitable for container/silo discharge flange Ø 250 mm 1 Shut-off valve with actuator and handwheel 2 Compressor is a dry running; no oil change needed 3 Control box for easy control and operation 4 Anti-tamper control by squeeze valve, the bypass technology allows filling of the conveying pot during the conveying process 5 Device for venting Easy replacement of wear parts - also on site Long machine running times with a high level of operational reliability Hard-moving materials with low filling height Rotary compressor: as rollable and portable execution available PFT praktische Tip Mount the extension hopper on the G 4 and take advantage of the maximum storage capacity (for premixed dry mortar).
 <p>3 Control box for easy control and operation</p> <p>5 Device for venting</p>	 <p>4 Anti-tamper control by squeeze valve, the bypass technology allows filling of the conveying pot during the conveying process</p>	
 <p>1 Shut-off valve with actuator and handwheel</p>		

FIELDS OF APPLICATION	
■ Machine-applied gypsum plaster	■ Masonry mortar
■ Gypsum-lime plaster	■ Bulk material
■ Cement render	■ Aggregate
■ Lime plaster	■ Ingredients
■ Lime cement plaster	and many more

ACCESSORIES	PART NO.
■ Conveying hose - initial equipment - 73.3 m, consisting of	00473424
• 1 x Rubber conveying hose RONDO air 3-layer DN45 - 13,3 m	
• 3 x Rubber conveying hose RONDO air 3-layer DN45 - 20 m	
• Hose holder with hook	
■ Extension cable 5 x 4 mm ² , RED 5-32 A - 50 m	20423900
■ Injection hood, foldable for G 4	00420664
■ Filling hopper for bagged goods	20716000
■ Extension hopper - 142 litres	00453469

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SILOMAT XXL-D - EN/10.22/PFT