


PFT G 4 super

The power package for your construction site

Designed for the use with SILOMAT and silo systems. This machine offers a customized solution for every construction site and ensures continuous operation thanks to the integrated level sensor. The changeable pump system allows use of powerful D and R pumps. This ensures many valuable production advantages on site.

TECHNICAL DATA

Part no.	00414171
Conveying output	max. 85 l/min
Conveying distance	up to 50 m
Working pressure	max. 30 bar
Rotor/ Stator	TWISTER D 6-3
Motor	400 V, 3 Ph, 50 Hz, 6.05 kW, 400 rpm
Material outflow	DN35 female part
Material hose	RONDO DN25 - 15 m
Water pump	AV 1000 400 V, 3 Ph, 50 Hz, 0.6 kW
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW, 250 l/min
Spraying gun	DN25-360° S14 200 Geka
Air hose	DN12 Ewo Geka - 15 m
Filling height	910 mm
Hopper content	145 l
Dimensions: L/W/H	1,200/720/1,530 mm
Weight	~ 310 kg



ADVANTAGES AT A GLANCE



- 1** Easy cleaning - rubber mixing zone with adapter flange for D and R pump
 - 2** Reinforced tubular frame and robust wheel mounts
 - 3** Forklift straps and crane lifting eyes
 - 4** Deflector - prevents whirling currents in the container
 - 5** Large control unit - maintenance-friendly and dust protection
 - 6** Switches and connectors are within the basic frame
 - 7** Large fine mesh water filter
 - 8** Practically transport safety for the mixing tube, reduce the high of the machine
 - 9** Easy, fast and efficient - the filling of the machine with material:
 - Direct filling from silo by using the delivery hood
 - Filling with bagged cargo
 - Pneumatic filling from silo by using conveying equipment PFT SILOMAT
- Flexible mixing intensity thanks to two water inlets
 - Safe transport thanks to four holders with folding mechanism
 - Maintenance-friendly - water manifold and pressure switch are easily accessible
 - Level sensor in the material hopper prevents the machine from idling

FIELDS OF APPLICATION

- Gypsum plaster
- Lime-gypsum plaster
- Cement plaster
- Lime plaster
- Lime-cement plaster
- Fango material
- Injection mortar
- Insulation plaster
- Recessed material
- Masonry mortar
- Floor screed
- Levelling compound
- Adhesive mortar

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A - 50 m
- DUSTCATCHER G 4 complete
- Injection hood with level sensor and control cable
- Delivery hood
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo

PART NO.

- 20423900
- 00539716
- 20600213
- 00471874
- 00420058
- 00418975



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360_G4
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT G 4 super - EN/10.22/PFT