

PFT RITMO XL

The powerful mixing pump for plastering


Compact and handy mixing pump with three-phase drive. Specially developed for pumping, spraying and applying ready-mixed dry mortars, pasty materials and much more.



TECHNICAL DATA

Part no.	00 18 64 78
Working pressure	30 bar
Conveying capacity	20 l/min
Conveying distance	up to 50 m
Motor	400 V, 3 Ph, 50 Hz, 5.5 kW, 400 rpm
Hopper content	70 l
Rotor/Stator	TWISTER D 6-3
Spraying gun	DN25-360° S14 200 Geka
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW - 250 l/min
Water pump	Water pressure booster pump AV 700, 400 V, 3 Ph, 50 Hz
Material outflow	DN25 male part
Material hose	RONDO DN25 - 10 m
Mixing tube	Rubber
Dimensions: L/W/H	1,300/700/1,400 mm
Filling height	850 - 1,010 mm
Weight	~ 224 kg

Kindly note:
All details depends on the used materials.



ADVANTAGES AT A GLANCE



- 1 Suitable for buckets and bags
- 2 Rubber mixing tube for easy cleaning with changeable flange for D- and R-pumps
- 3 Flexible mixing intensity thanks to two water inlets
- Conical mixing tube for optimum material flow
- Ready for remote control cable
- Integrated water pump AV 700 as water pressure booster pump
- Easy, compact and rollable
- Variable filling height
- Easy dismountable into three modules

FIELDS OF APPLICATION

- Premixed gypsum plaster
- Lime gypsum plaster
- Cement plaster
- Masonry mortar
- Reinforcing / adhesive mortar
- Insulation plaster
- Floor screed



ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A - 25 m
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo
- Spraying set for finishing coats in case
- Extension hopper - 140 litres
- Cover for RITMO XL

PART NO.

- 20 42 39 20
- 00 42 00 58
- 00 41 89 75
- 00 23 21 06
- 00 20 18 70
- 00 20 79 57



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT RITMO XL - EN/03.21/PFT