

SD 6-3 slimline SD 6-3 slimline soft

The big ones for powerful 230 V machines from PFT

The PFT rotor/stator system has been specially developed for use in 230 V machines from PFT, such as the G 4 FC-230/400V. Due to the conveying output of 20 l/min and a grain size up to 3 mm, the big ones integrate perfectly into the PFT rotor/stator family.



TECHNICAL INFORMATION

SD 6-3 slimline

Stator	00 40 62 89
Rotor	00 40 62 88
Conveying output	up to 20 litres / min
Conveying pressure	max. 20 bar
Conveying distance	up to 20 m
Grain size	max. 2 mm
Rubber hardness	hard
Stator type	maintenance-free
Connection type / Ø	D pump / 90 mm
Stator length	273 mm

SD 6-3 slimline soft

Stator	00 58 50 53
Rotor	00 40 62 88
Conveying output	up to 20 litres / min
Conveying pressure	max. 15 bar
Conveying distance	up to 20 m
Grain size	max. 2 mm
Rubber hardness	soft
Stator type	maintenance-free
Connection type / Ø	D pump / 90 mm
Stator length	273 mm

ADVANTAGES AT A GLANCE

- high conveying output
- hose length up to 20 m
- highly wear resistant rubber compound
- highly wear-resistant rotor made of hard chromium carbide cast iron

Please note:

Standard values depending on mortar quality, mortar composition, mortar consistency, pump version, pump condition, material hose diameter and delivery height. Ultimately, the respective guidelines of the material manufacturer are decisive.

