


PFT G 4 screed

The powerful screed professional










The PFT G 4 screed is the effective solution for professional use on the construction site. The powerful star wheel and the special BIONIK mixing shaft in combination with the tensionable R-pump guarantee the smooth execution of screed work. The integrated ROTOMIX agitator also enables the machine to crush lumps.

TECHNICAL DATA

| | |
|--------------------------|--|
| Part no. | 00425100 |
| Conveying output | max. 85 litre / min |
| Conveying distance | up to 50 m |
| Working pressure | max. 15 bar |
| Rotor / Stator | R 8 - 1,5 clampable Agitator: ROTOMIX |
| Motor | 400 V, 3 Ph, 50 Hz, 6,05 kW, 400 rpm |
| Material outflow | DN35 male part |
| Material hose | RONDO DN35 Watering hose - 20 m |
| Water pump | AV 1000 400 V, 3 Ph, 50 Hz, 0.6 kW |
| Water flow meter | 250 - 2,500 l/h |
| Filling height | 910 mm |
| Hopper content | 145 litre |
| Dimensions: L / W / H | 1,200 / 720 / 1,530 mm |
| Weight | ~ 300 kg |



ADVANTAGES AT A GLANCE

| | | | |
|--|---|--|---|
|  |  |  | <p>1 Professional processing of floor screed through special BIONIK mixing shaft</p> <p>2 High performance through powerful star wheel</p> <p>3 Intensive mixing with the PFT ROTOMIX post-mixer makes the mortar smoother, more productive and knot-free</p> |
|  |  |  | <p>4 Deflector plate - Reduction of dust exposure</p> <p>5 Large control unit - maintenance-friendly and dust protection</p> <p>6 Reinforced tubular frame and robust wheel mounts</p> |
|  |  |  | <p>7 Smooth operation through large fine mesh water filter</p> <p>8 Practically transport safety for the mixing tube, reduce the high of the machine</p> <p>9 Easy, fast and efficient - the filling of the machine with material: - Direct filling from silo by using the delivery hood - Filling with bagged cargo - Pneumatic filling from silo by using conveying equipment PFT SILOMAT</p> |

- Flexible mixing intensity thanks to two water inlets
- Safe transport thanks to four holders with folding mechanism
- Maintenance-friendly - water manifold and pressure switch are easily accessible
- Switches and connectors are within the basic frame

FIELDS OF APPLICATION

- Floor screed
- Levelling compensation mass
- Flow filler

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A - 50 m
- Extension hopper - 70 litres
- Delivery hood

PART NO.

20423900
00436020
00471874



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360_G4
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT G 4 screed - EN/04.23/PFT