

# PFT HM 2002

## The compact continuous mixer for large capacities

Quickly ready for use, reliable, powerful, easy to operate – the compact continuous mixer PFT HM 2002 for bagged goods. It continuously and fully automatically mixes all lime/cement based factory dry mortars up to a maximum grain size of 4 mm.



### TECHNICAL DATA

Part no.	00 02 04 73
Mixing capacity*	30 l/min Dosing shaft: 30 l/min
Motor	230 V, 1 Ph, 50 Hz, 2.2 kW, 280 rpm
Mixing tube	Rubber mixing tube
Grain size	max. 4 mm
Electrical connection	Fuse rating: 16 A
Water connection	DN12 (1/2") 2.5 bar working pressure
Wheels	2 wheels
Operation and control	Start/Stop
Pedestal	fix
Hopper content	110 litre
Dimensions: L / W / H	1,870/600/1,040 mm
Filling height	1,000 mm
Output height	600 mm
Weight	~ 100 kg


\*Standard values depending on mortar quality, mortar composition, mortar consistency, pump model, pump condition, material hose diameter and feed height. Mixing capacity can vary depending on the dosing shaft used. The guidelines of the material manufacturer are ultimately authoritative.



230 V



2.2 kW



1 Ph



30 l/min

## ADVANTAGES AT A GLANCE







- 1** Low filling height
- 2** Secured quick release fastener
- 3** Maintenance-free square outer bearing
- 4** Rubber mixing tube
  - Perfectly suitable for the application of glueing mortars
  - No permanent material sticking
  - Improved mixing quality
  - Easy and intensive cleaning
  - Low wear and tear
  - Inexpensive wearing part
- 5** Robust design
  - Easy operation
  - Minimal maintenance and cleaning overhead
  - Easy to dismantle into individual parts for convenient transport
  - Removeable special mortar outlet

### FIELDS OF APPLICATION

- Masonry and light masonry mortar
- Facing mortar
- Scratch coat
- Cement plaster
- Insulation plaster
- Screed mortar
- Tilling and jointing mortar
- Glueing and reinforcing mortar
- Levelling compound
- Grater mortar
- Lime plaster
- Restoration plaster
- High-grade plaster

### ACCESSORIES

	PART NO.
■ Extension cable 3 x 2,5 mm <sup>2</sup> , BLA 2-16 A - 25 m**	20 42 34 00
■ Water hose/air hose DN19 Geka   Geka - 40 m**	20 21 21 00
■ Water hose/air hose DN12 Geka   Geka - 5 m	20 21 11 00
■ Spray nozzle DN19 Geka	20 21 57 00
■ Retrofit kit for water flow meter 100 - 1.000 l/h	00 00 10 91
■ Cover for material hopper	00 20 67 10

\*\* necessary accessories for commissioning

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpften](http://www.youtube.com/knaufpften)

Download now! APP: PFT - Plastering Technology

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT HM 2002 - EN/03.20/PFT