

PFT LOTUS XXL bag


The continuous mixer that simply mixes everything

Due to an excellent mixing output capacity of 90 l/min and a grain size of 16 mm, the horizontal continuous mixer PFT LOTUS XXL bag is unbeatable. The machine can be loaded directly with a delivery hood in just a few steps.

TECHNICAL DATA

Part no.	00 60 91 45
Conveying capacity	max. 90 litres / min
Motor	400 V, 3 Ph, 50 Hz, 7.5 kW, 254 rpm
Mixing tube	Rubber
Grain size	max. 16 mm
Wheels	2 wheels
Water connection	Geka DN19 (3/4") 2.5 bar operating pressure
Operation	Start / stop Auto-stop by sensor control
Hopper volume	110 litres
Dimensions: L / W / H	2,545 / 770 / 1,175 mm
Filling height	1,175 mm
Output height	620 mm
Weight	~255 kg

Please note:
Mixing output capacity depends on the used materials.



PFT – ALWAYS AT YOUR SITE

ADVANTAGES AT A GLANCE



- 1 Reach-in protected, dismantable grout outlet
- 1 Easy to transport – handle on mixing tube
- 2 Automatic stop mechanism through dry and wet sensor control
- 3 Conveying pump, mortar bucket or wheelbarrow can be easily placed underneath
- Fill level monitoring of dry container (via control box)
- Rubber mixing tube
- Bag mixer for stiff material
- Stable base frame
- Water fitting and water flow meter 150 - 1.500 l/h
- Minimal maintenance and cleaning effort
- Constant mixing quality
- Easy operation through control box

FIELDS OF APPLICATION

- Concrete screed
- Masonry mortar (for industrial applications)
- Insulation plaster
- Ready-mixed concrete (up to 8 mm grain size)

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A – 25 m
- Water hose Geka | Geka DN19 – 40 m
- Water pump as suction pump AV 1000 standalone
- Dosing shaft 60 l/min
- Extension hopper – 142 litres
- Delivery hood

PART NO.

- 20 42 39 20
- 20 21 21 00
- 00 49 36 86
- 00 62 31 93
- 00 45 34 69
- 20 60 05 00

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT LOTUS XXL bag – EN/09.20/PFT