

PFT G 4 switch rs


Powerful and compact

The mixing pump is designed for tough work without compromises. Higher motor power, conveying output and conveying distance leave no desires unfulfilled.



TECHNICAL DATA

Part no.	00775226
Working pressure	max. 40 bar
Conveying output (at 400 V)	max. 35 l/min
Conveying distance	up to 50 m
Motor	230/400 V, 1/3 Ph, 50 Hz, 6.05 kW, 400 rpm
Rotor/Stator	SD 6-3 slimline
Spraying gun	DN25-360° S14 600-30° Geka
Air compressor	COMP P-200, 230 V, 1 Ph, 50 Hz, 0.52 kW, 200 l/min
Material outflow	DN35 male part
Material hose	RONDO DN25 - 15 m + RONDO superlight flex DN25 - 5 m
Operation	Start/stop incl. idle protection via capacitive sensor
Hopper content	145 l
Dimensions: L / W / H	1.200 / 720 / 1.530 mm
Filling height	910 mm
Weight	~365 kg



ADVANTAGES AT A GLANCE



- 1** Easy cleaning – rubber mixing zone with adapter flange for D and R pump
- 2** Reinforced tubular frame and robust wheel mounts
- 3** Forklift straps and crane lifting eyes
- 4** Deflector – prevents whirling currents in the container
- 5** Large control box – easy to maintain and dust protection
- 6** Switches and connectors are within the basic frame
- 7** Trouble-free operation due to large fine mesh water filter
- 8** Easy, fast and efficient – the filling of the machine with material:
 - Filling with bagged cargo
 - Pneumatic filling from silo by using conveying equipment PFT SILOMAT
- Flexible mixing intensity thanks to two water inlets
- Safe transport thanks to four holders with folding mechanism
- Perfectly maintenance-friendly – smooth accessibility of the tap fittings and press switches
- Run-empty safeguard in material hopper – it prevents the empty running of the machine

FIELDS OF APPLICATION

- Gypsum plasters
- Lime-gypsum plaster
- Cement plaster
- Insulation material
- Lime-cement plaster
- Fango materials
- Insulation plaster
- Recessed mortar
- Masonry mortar
- Floor screed
- Levelling compound
- Adhesive mortar

ACCESSORIES

- | | |
|---|----------|
| ■ Extension cable 5 x 4 mm ² , RED 5-32 A – 50 m | 20423900 |
| ■ Injection hood with level sensor and control cable | 20600213 |
| ■ ZARGOMAT pro DN25-360° | 00420058 |
| ■ JETSET pro DN25 Ewo | 00418975 |
| ■ Spraying set for finishing coat | 00232106 |

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photo-mechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT G 4 switch rs – DE/09.22/PFT