

PFT G 4 smart sp


Convincing quality for perfect work

For every challenge, the PFT G 4 smart sp offers an efficient and reliable solution in tough daily use. Equipped with level sensor in the material hopper - prevents the machine from running empty.



TECHNICAL DATA

Part no.	00764411
Conveying output	max. 35 l/min
Conveying distance	up to 30 m
Working pressure	max. 30 bar
Rotor/Stator	D 6-3 mf
Motor	400 V, 3 Ph, 50 Hz, 6.05 kW, 400 rpm
Material outflow	DN35 female part
Operation and control	Start/Stop incl. water pump control
Material hose	RONDO DN25 - 10 m RONDO superlight plus DN25 - 10 m
Water pump (p)	AVO 500 400 V, 3 Ph, 50 Hz, 0.37 kW
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW, 250 l/min
Spraying gun	DN25-360° S14 200 Geka
Water / air hose	DN19 Geka Geka - 20 m
Air hose	DN12 Ewo male part Geka - 11 m DN13 Geka Geka - 11 m
Filling height	910 mm
Hopper content	145 liters
Dimensions: L / W / H	1,200 / 720 / 1,530 mm
Weight	~295 kg



ADVANTAGES AT A GLANCE



- 1** Large fine mesh water filter
- 2** Reinforced tubular frame and robust wheel mounts
- 3** Forklift straps and crane lifting eyes
- 4** Easy, fast and efficient – the filling of the machine with material:
 - Direct filling from silo by using the delivery hood
 - Filling with bagged cargo
 - Pneumatic filling from silo by using conveying equipment PFT SILOMAT and injection hood
- 5** PFT DUSTCATCHER to reduce dust formation
- 6** Level sensor (s) in material hopper – it prevents the empty running of the machine
- Switches and connectors are within the basic frame
- Flexible mixing intensity thanks to two water inlets
- Safe transport thanks to four holders with folding mechanism
- Maintenance-friendly – water manifold and pressure switch are easily accessible

FIELDS OF APPLICATION

- Gypsum plaster
- Lime-gypsum plaster
- Cement plaster
- Insulation material
- Lime-cement plaster
- Fango material
- Insulation plaster
- Recessed material
- Masonry mortar
- Floor screed
- Levelling compound
- Adhesive mortar

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A – 50 m
- DUSTCATCHER G 4 complete
- Injection hood
- Delivery hood
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo

PART NO.

- 20423900
- 00539716
- 20600213
- 20600500
- 00420058
- 00418975

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT G 4 smart sp – EN/04.23/PFT