

RITMO L FC-230V smart with water pressure booster pump


One-person solution for small construction sites without constant water supply

The small mixing pump PFT RITMO L smart offers maximum performance for little money. The entry-level machine developed for the most common applications is equipped with a booster pump. This ensures constant water pressure and guarantees continuous working.




TECHNICAL DATA

Part no.	00790474
Conveying output	2 - 14 l/min, continuously adjustable
Conveying distance	up to 20 m
Operating pressure	max. 20 bar
Rotor/Stator	B 4-2
Motor	230 V, 1 Ph, 50 Hz, 2.4 kW, 74 - 492 rpm
Mixing tube	Steel
Material outflow	DN25 male part
Material hose	RONDO DN25 - 10 m
Water flow meter	75 - 750 l/h
Water connection	Geka DN12 (1/2") - 2.5 bar working pressure
Water pump for Pressure increase	AVO 500, 230 V, 1 Ph, 50 Hz, 0.37 kW
Operation and control	Start/stop and continuously adjustable speed control
Air compressor	COMP R-80, 230 V, 1 Ph, 50 Hz, 0.35 kW, 80 l/min
Air hose	DN9 Ewo Ewo - 16 m
Spraying gun	smartline DN25 S10 200 Ewo, air nozzle tube 4 mm
Filling height	930 mm
Hopper content	45 l
Dimensions: L / W / H	920 / 600 / 1,420 mm
Weight	~110 kg



ADVANTAGES AT A GLANCE



- 1** Large throw-in area
- 1** Material container for constant flow rate
- encourages ergonomic work
- 2** Control cabinet
- the latest technology
- 3** Mortar pressure gauge
- easy to read the working pressure
- 3** Flow-optimised outlet
- prevents kinks and constrictions
and the risk of clogging
- Water pump**
- trouble-free operation of the machine
with low water pressure
- Water flow meter** 75 - 750 l/h
- Simple operation of the frequency converter**
- Easy to dismantle into three modules**
- Pump motor with protective grille
- Chassis
- Material container
- Transport is possible in any estate car**
- Runs powerfully and reliably with luminous flux**
- Cleaner coupling 25 male part | Geka**
For cleaning the mortar hose
- Easy handling during commissioning,
conversion, maintenance and cleaning**

FIELDS OF APPLICATION

- Interior plaster
- Finishing coat
- Floor levelling compound
- Spachtelmasse
- Filler
- Adhesive and reinforcing mortar
- Frame grouting mortar

ACCESSORIES

- Extension cable 3 x 2.5 mm²,
BLU 3-16 A | BLA 2-16 A - 25 m
- Water hose/air hose
DN12 Geka | Geka - 11 m
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo
- Spraying set for finishing coat
- Extension hopper - 75 Liter
- Water pump as suction pump
AV 1000 standalone, 230 V, 1 Ph, 50 Hz, 0.6 kW

PART NO.

- 20423420
- 20211000
- 00420058
- 00418975
- 00232106
- 00089793
- 00493686

The PFT Service-Guarantee

The PFT service guarantee Customer proximity, technical competence and service orientation. This is what PFT stands for with its sales and service centres around the world in the decades to come.



click. discover. experience.
www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technische Hotline +49 9323 31-1818

Telefon +49 9323 31-760

Telefax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

RITMO L smart 00790474 - EN/10.23/PFT